SPEED QUEEN ON-PREMISES LAUNDRY


FCU13X82 HEATED ROLL FLATWORK FINISHER

Heated Roll Flatwork Finisher

When "good enough" isn't good enough, our rollheated ironers are ready to get the job done. Top-notch performance that includes safety features to match. With a wide range of electric or gas models, these machines are guaranteed to get the job done quickly, efficiently and effectively. On-premises laundries at hotels, restaurants and other sites who rely on the highest quality results will benefit from excellent final linen products and reduced operating costs.

- Constructed with heavy-duty steel frames and cylinders.
- Low maintenance.
- Easy and safe features like feeding trays, stop bars and alarms make operation both safe and simple.
- Low BTU consumption so ensure consistent temperature for energy efficiency.






Micro Control

Efficient and user-friendly, our Micro Control enables you to regulate temperature and reduce energy consumption.



SPECIFICATIONS HEATED ROLL FLATWORK FINISHER

MODEL PC013X82 ROLL DIAMETER - in (mm) 13 (320) FINISHING WIDTH - in (mm) 82 (2080) IRONING SPEED - ft/m (m/m) 3-20 (1-6) IRONER DIMENSIONS (working position) - in (mm) Width 102 3/4 (2610) Depth 30 (765) Height 43 3/4 (110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 279 Electric Requirements - Circuit Breaker 230/60/3 - 80 GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) Gas Inlet - in (mm) 3/4 (19) Electric Requirements - Circuit Breaker 120/60/1 - 15 230/60/1 - 15 230/60/1 - 15 SHIPPING Height 49 5/8 (1260) 1012 3/4 (2610) 23/4 (2610) DIMENSIONS - in (mm) Width 102 3/4 (2610) 23/4 (2610) SHIPPING Electric 1235 (560) 23/4 (2610) WEIGHT - Ib (kg) Gas 1191 (540) 1025 (465)	MODEL		FOU12X92
FINISHING WIDTH - in (mm) 82 (2080) IRONING SPEED - ft/m (m/m) 3-20 (1-6) IRONER DIMENSIONS (working position) - in (mm) Depth 30 (765) Height 43 3/4 (110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW Z99 Electric Requirements- Circuit Breaker GAS HEATING Max. Gas Input - Btu (kW) DUC/0.1 - 15 230/60/3 - 80 SHIPPING Height DIMENSIONS - in (mm) Width Width 102 3/4 (2610) Depth 31 1/2 (800) SHIPPING WEIGHT - Ib (kg) Electric WEIGHT - Ib (kg) Electric Gas 1191 (540)			FCU13X82
IRONING SPEED - ft/m (m/m) 3-20 (1-6) IRONER DIMENSIONS (working position) - in (mm) Width 102 3/4 (2610) Depth 30 (765) Height 43 3/4 (1110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 27.9 Electric Requirements - Circuit Breaker 230/60/3 - 80 GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) Gas Inlet - in (mm) 3/4 (19) 120/60/1 - 15 SHIPPING DIMENSIONS - in (mm) Width 102 3/4 (2610) Depth 31 1/2 (800) 102 3/4 (2610) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) WEIGHT - Ib (kg) Electric 1080 (490) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465) 1025 (465)	ROLL DIAMETER - in (mm)		13 (320)
IRONER DIMENSIONS (working position) - in (mm) Width 102 3/4 (2610) Depth 30 (765) Height 43 3/4 (110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 27.9 230/60/3 - 80 Circuit Breaker 230/60/3 - 80 230/60/3 - 80 230/60/3 - 80 GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) 3/4 (19) Electric Requirements- Circuit Breaker 120/60/1 - 15 120/60/1 - 15 SHIPPING DIMENSIONS - in (mm) Width 102 3/4 (2610) 102 3/4 (2610) Depth 31 1/2 (800) 11/2 (800) 11/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465)	FINISHING WIDTH - in (mm)		82 (2080)
(working position) - in (mm) Depth 30 (765) Height 43 3/4 (1110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 279 Electric Requirements - Circuit Breaker 230/60/3 - 80 30 (765) GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) 34 (19) Electric Requirements - Circuit Breaker 120/60/1 - 15 120/60/1 - 15 SHIPPING DIMENSIONS - in (mm) Width 102 3/4 (2610) Depth 31 1/2 (800) 31 1/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) WEIGHT - Ib (kg) Electric 1080 (490) NET WEIGHT - Ib (kg) Electric 1080 (490)	IRONING SPEED - ft/m (m/m)		3-20 (1-6)
Depth 30 (765) Height 43 3/4 (110) ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 27.9 Electric Requirements - Circuit Breaker 230/60/3 - 80 230/60/3 - 80 GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) 34 (19) Electric Requirements - Circuit Breaker 120/60/1 - 15 120/60/1 - 15 SHIPPING Height 49 5/8 (1260) 102 3/4 (2610) DIMENSIONS - in (mm) Width 102 3/4 (2610) 102 3/4 (2610) SHIPPING Electric 1235 (560) 1235 (560) WEIGHT - Ib (kg) Electric 1080 (490) 1025 (465)		Width	102 3/4 (2610)
ROLL MOTOR - HP (kW) 0.24 (0.18) EXHAUST MOTOR - HP (kW) 0.17 (0.125) EXHAUST MOTOR - HP (kW) 6 (150) EXHAUST DUCT - in (mm) 6 (150) ELECTRIC HEATING E Heat Input Power - kW 27.9 Electric Requirements- Circuit Breaker 230/60/3 - 80 230/60/3 - 80 GAS HEATING Max. Gas Input - Btu (kW) 102,364 (30) 3/4 (19) Electric Requirements- Circuit Breaker 120/60/1 - 15 120/60/1 - 15 SHIPPING DIMENSIONS - in (mm) Height 49 5/8 (1260) Dimensions - in (mm) Width 102 3/4 (2610) Depth 31 1/2 (800) 31 1/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) WEIGHT - Ib (kg) Electric 1080 (490) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465) 1025 (465)	(working position) - in (mm)	Depth	30 (765)
EXHAUST MOTOR - HP (kW)0.17 (0.125)EXHAUST DUCT - in (mm)6 (150)ELECTRIC HEATINGE Heat Input Power - kW279Electric Requirements - Circuit Breaker230/60/3 - 80GAS HEATINGMax. Gas Input - Btu (kW)102,364 (30)Gas Inlet - in (mm)3/4 (19)Electric Requirements - Circuit Breaker120/60/1 - 15SHIPPINGHeight49 5/8 (1260)DIMENSIONS - in (mm)Width102 3/4 (2610)SHIPPING WEIGHT - Ib (kg)Electric1235 (560)WEIGHT - Ib (kg)Electric1080 (490)NET WEIGHT - Ib (kg)Electric1080 (490)Gas1025 (465)1025 (465)		Height	43 3/4 (1110)
EXHAUST DUCT - in (mm)6 (150)ELECTRIC HEATINGE Heat Input Power - kW27.9Electric Requirements - Circuit Breaker230/60/3 - 80GAS HEATINGMax. Gas Input - Btu (kW)102,364 (30)Gas Inlet - in (mm)3/4 (19)Electric Requirements - Circuit Breaker120/60/1 - 15SHIPPING DIMENSIONS - in (mm)Height49 5/8 (1260)DIMENSIONS - in (mm)Width102 3/4 (2610)Depth311/2 (800)311/2 (800)SHIPPING WEIGHT - Ib (kg)Electric1235 (560)NET WEIGHT - Ib (kg)Electric1080 (490)Gas1025 (465)1025 (465)	ROLL MOTOR - HP (kW)		0.24 (0.18)
ELECTRIC HEATINGE Heat Input Power - kW27.9Electric Requirements- Circuit Breaker230/60/3 - 80GAS HEATINGMax. Gas Input - Btu (kW)102,364 (30)Gas Inlet - in (mm)3/4 (19)Electric Requirements- Circuit Breaker120/60/1 - 15SHIPPING DIMENSIONS - in (mm)Height49 5/8 (1260)UMENSIONS - in (mm)Width102 3/4 (2610)Depth311/2 (800)31 1/2 (800)SHIPPING WEIGHT - Ib (kg)Electric1235 (560)WEIGHT - Ib (kg)Gas1191 (540)NET WEIGHT - Ib (kg)Electric1080 (490)Gas1025 (465)1025 (465)	EXHAUST MOTOR - HP (kW)		0.17 (0.125)
Electric Requirements- Circuit Breaker230/60/3 - 80 Circuit BreakerGAS HEATINGMax. Gas Input - Btu (kW)102,364 (30) Gas Inlet - in (mm)Gas Inlet - in (mm)3/4 (19)Electric Requirements- Circuit Breaker120/60/1 - 15 Circuit BreakerSHIPPING DIMENSIONS - in (mm)Height49 5/8 (1260) 102 3/4 (2610) DepthSHIPPING DIMENSIONS - in (mm)Width102 3/4 (2610) 102 3/4 (2610) DepthSHIPPING WEIGHT - Ib (kg)Electric1235 (560) (191 (540)NET WEIGHT - Ib (kg)Electric1080 (490) GasIntervence Gas1025 (465)	EXHAUST DUCT - in (mm)		6 (150)
Circuit BreakerGAS HEATINGMax. Gas Input - Btu (kW)102,364 (30)Gas Inlet - in (mm)3/4 (19)Electric Requirements - Circuit Breaker120/60/1 - 15SHIPPING DIMENSIONS - in (mm)Height49 5/8 (1260)Dimension Width102 3/4 (2610)102 3/4 (2610)Bettertic WEIGHT - Ib (kg)Electric1235 (560)NET WEIGHT - Ib (kg)Electric1080 (490)Gas1025 (465)1025 (465)	ELECTRIC HEATING	E Heat Input Power - kW	27.9
Gas Inlet - in (mm) 3/4 (19) Electric Requirements- Circuit Breaker 20/60/1 - 15 Electric Requirements- Circuit Breaker 49 5/8 (1260) DIMENSIONS - in (mm) Width 102 3/4 (2610) Depth 311/2 (800) Electric 1235 (560) WEIGHT - Ib (kg) Gas 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465)			230/60/3 - 80
Electric Requirements- Circuit Breaker 120/60/1 - 15 SHIPPING DIMENSIONS - in (mm) Height 49 5/8 (1260) Width 102 3/4 (2610) 102 3/4 (2610) Depth 311/2 (800) 311/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465) 1025 (465)	GAS HEATING	Max. Gas Input - Btu (kW)	102,364 (30)
Circuit Breaker SHIPPING DIMENSIONS - in (mm) Height 49 5/8 (1260) Width 102 3/4 (2610) 102 3/4 (2610) Depth 31 1/2 (800) 11/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) WEIGHT - Ib (kg) Gas 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465) 1025 (465)		Gas Inlet - in (mm)	3/4 (19)
DIMENSIONS - in (mm) Width 102 3/4 (2610) Depth 31 1/2 (800) SHIPPING Electric 1235 (560) WEIGHT - lb (kg) Gas 1191 (540) NET WEIGHT - lb (kg) Electric 1080 (490) Gas 1025 (465)			120/60/1 - 15
Width 102 3/4 (2610) Depth 31 1/2 (800) SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) Gas 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465)		Height	49 5/8 (1260)
SHIPPING WEIGHT - Ib (kg) Electric 1235 (560) NET WEIGHT - Ib (kg) Gas 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465) 1025 (465)	DIMENSIONS - IN (MM)	Width	102 3/4 (2610)
WEIGHT - lb (kg) Gas 1191 (540) NET WEIGHT - lb (kg) Electric 1080 (490) Gas 1025 (465)		Depth	31 1/2 (800)
Gas 1191 (540) NET WEIGHT - Ib (kg) Electric 1080 (490) Gas 1025 (465)		Electric	1235 (560)
Gas 1025 (465)	WEIGHT - Ib (Kg)	Gas	1191 (540)
	NET WEIGHT - Ib (kg)	Electric	1080 (490)
AGENCY APPROVALS CSA		Gas	1025 (465)
	AGENCY APPROVALS		CSA



Α.	WIDTH - in (mm)	102 3/4 (2610)
В.	DEPTH - in (mm)	30 (765)
C.	HEIGHT - in (mm)	43 3/4 (1110)

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.



