

ON-PREMISES LAUNDRY

Commercial Washers and Dryers







DEDICATED TO A HIGHER STANDARD.

Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.

We believe that strength comes from within. Speed Queen machines are built specifically for the commercial environment. We use metal where others use plastic. Our world-class Test Lab rigorously pushes our products far beyond the conditions they'll face in the field. We go the extra mile at every point of our manufacturing process to ensure that our machines are built better to last longer.

For commercial laundry equipment designed for use in fire departments, health care facilities, hotels, correctional facilities, spas, salons, athletics organizations or another industry application, you can rely on the proven performance of Speed Queen to make your life simpler and more productive.



CONTROL OPTIONS

ELECTRONIC HOMESTYLE

Speed Queen washers and dryers with Electronic Homestyle Control are designed for durability and easy to operate with intuitive selection buttons and cycle status indicator lights. It features a time-remaining display, six preset cycle buttons, cycle adjustability for temperature, load size and soil levels along with additional cycle enhancer options for a pre-wash or second rinse cycle. Available on all front load washer, top load washer, dryer, stack dryer and stack washer/dryer.

E-MECH

Speed Queen washers and dryers with E-Mech controls are designed for durability and ease of use with push to start switch and reinforced control knobs. It offers customers a straight-forward design with simple temperature and fabric selections and includes indicator lights to keep customers aware of what cycle the machines are in. Available on rear control front load washer, top load washer, rear control dryer and stack dryer.

BUILT FOR RELIABLE PERFORMANCE.



FRONT LOAD WASHER

Shown with Electronic Homestyle Control

Revolutionary balancing technology redistributes unbalanced load for uninterrupted wash cycles

Increase spin speed extracts 440 G-Force to maximize moisture removal and lower drying times

20% increase in capacity with improved water usage to decrease operating costs

Redesigned 4-compartment soap dispenser for simplified use and cleaning



Shown with E-Mech Control

Water level selectors give managers the flexibility to choose wash and rinse levels Extra-large capacity wash tub in stainless steel or porcelain Commercial quality transmission offers highest quality and durability Advanced suspension system eliminates the possibility of an unbalanced load issue





SINGLE AND STACK DRYER

Shown with Electronic Homestyle Control

Extra-large capacity with the largest door opening in the industry Front access for easy serviceability Stack unit offers two dryers in floor space of one Durable galvanized steel cylinder



MODELS	Front Load Washer	Front Load Washer	Top Load Washer	Single Dryer	Single Dryer	Stack Dryer	Stack Washer/Dryer
Available Controls	Electronic	Electronic	Electronic, E-Mech	Electronic	Electronic, E-Mech	Electronic, E-Mech	Electronic
Available Control Location	Front	Rear	Rear	Front	Rear	Front	Front
Capacity - Ib (kg)	21.5 (9.5)	21.5 (9.5)	16 (7.3)	18 (8.2)	18 (8.2)	18 (8.2)	See front control front load washer and dryer specs to left
Cylinder Volume - cu. Ft. (liters)	3.42 (96.8)	3.42 (96.8)	3.19 (90.3)	7.0 (198)	7.0 (198)	7.0 (198)	
Width - in (mm)	26.875 (683)	26.875 (683)	25.63 (651)	26.875 (683)	26.875 (683)	26.875 (683)	26.875 (683)
Depth - in (mm)	27.73 (704)	27.73 (704)	28 (711)	28 (711)	28 (711)	28 (711)	27.73 (704)
Height - in (mm)	40.42 (1027)	43 (1092)	43 (1092)	40.42 (1027)	43 (1092)	78.17 (1986)	78.17 (1986)
Spin Speed G-Force (RPM)	440 (1200)	440 (1200)	150 (710)	N/A	N/A	N/A	See front control front load washer and dryer specs to left
Motor Size - HP (kw)	Variable Speed Inc	luction 0.9 (0.67)	0.5 (0.37)	0.33 (0.25)	0.33 (0.25)	0.33 (0.25)	
Water Consumption per Cycle - g (I)*	13.68 (51.8)	13.68 (51.8)	27.9 (106)	N/A	N/A	N/A	
IWF (Water Factor)*	4.0	4.0	8.8	N/A	N/A	N/A	
IMEF (Modified Energy Factor)*	2.20	2.20	1.35	N/A	N/A	N/A	
Available Heat Sources	N/A	N/A	N/A	Gas or Electric	Gas or Electric	Gas or Electric	
Available Heating Element (Electric W)	N/A	N/A	N/A	5350 @ 240V	5350 @ 240V	5350 @ 240V	
Gas Inlet Connection - in (mm)	N/A	N/A	N/A	3/8 (9.5)	3/8 (9.5)	3/8 (9.5)	
Gas Consumption - BTU/Hr	N/A	N/A	N/A	22,500	22,500	22,500	
Exhaust Outlet Dia in (mm)	N/A	N/A	N/A	4 (102)	4 (102)	4 (102)	
Exhaust Airflow - cfm (liters/sec)	N/A	N/A	N/A		220 (105)		
Available Water Temperatures	3	3	3	N/A	N/A	N/A	
Available Cycles*	Heavy Duty, Normal Eco, Perm Press, Delicate, Rinse and Spin, Spin Only			Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up			
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	N/A	N/A	N/A	
Cycle Indicator Lights	Yes	Yes	Yes	Yes	Yes	Yes	
Cylinder Finish	Stainless Steel	Stainless Steel	Stainless Steel	Galvanized	Galvanized, White	Galvanized	
Available Colors	White	White	White	White	White	White	
Door Type (Solid/Window)	Window	Window	N/A	Solid	Solid	Solid or Window	Window
Available Electrical Requirements - (Voltage/Hz/Ph - Circuit Amperage)	120/60/1 - 15 Amp	120/60/1 - 15 Amp	120/60/1 - 15 Amp	Gas: 120/60/1 - 15 Amp, Electric: 120/240/60/1 - 30 Amp			See front control front load washed and dryer specs to left
Net Weight - Ib (kg)	260 (118)	260 (118)	186 (84)	Electric/Gas 126/130 (57/59)	Electric/Gas 126/130 (57/59)	Electric/Gas 262/270 (119/122)	385 (175)
Shipping Weight - Ib (kg)	270 (122)	270 (122)	196 (89)	Electric/Gas 136/140 (62/64)	Electric/Gas 136/140 (62/64)	Electric/Gas 272/280 (123/127)	417 (189)
Shipping Width - in (mm)	30 (762)	30 (762)	28 (711)	29.5 (749)	29.5 (749)	30 (762)	30 (762)
Shipping Depth - in (mm)	34 (864)	34 (864)	30 (762)	30.5 (775)	30.5 (775)	33 (838)	34 (864)
Shipping Height - in (mm)	44.5 (1130)	44.5 (1130)	45 (1143)	45 (1143)	45 (1143)	80 (2032)	80 (2032)
Available Agency Approvals ADA Compliant	cULus	cULus	cULus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus

Note: Not all options are available for all models. Refer to the price list for the available models and options.

*Information shown applies to highest end control available.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the USA.

